




MATERIAL HANDLING
FOOD



SPECIALISTS

“Always a
clean solution.”

Paul, 46, Head of Engineering Design

PU approved
to EU compliance
10/2011 and FDA

IN WORLDWIDE USE

As an experienced partner in the food and beverage industry, Optibelt has the ideal drive solution to meet even the most demanding requirements. This means that every processing step – from packaging and sorting through to transport – runs smoothly and with absolute precision. Additional factors that find approval with customers and users alike include exemplary efficiency and minimised maintenance costs. This is why Optibelt's sustainable premium products can be found in use around the globe.

FOR THE FOOD INDUSTRY

OPTIBELT SUCCESS STORY

A CLEAN SOLUTION



MIHO, based in northern Hesse in Germany, is a leading manufacturer of empty bottle inspection systems for the beverage industry. The company had been experiencing problems with the open-pore coating of the transport belts in the camera-controlled inspection systems. The coating was absorbing too much moisture, resulting in defective goods and bacteriological contamination. So, in cooperation with Optibelt, a new sandwich coating was developed using a neoprene foam combined with a dimpled PVC membrane. This system has shown itself to be optimally effective in practice.

OPTIBELT SUCCESS STORY

SAFE INDULGENCE THANKS TO OPTIBELT

Whether for pizza or chocolate – these two products have one thing in common: Firstly, they are popular products found in shopping baskets worldwide, and secondly, they come “into contact” with **optibelt ELASTOMIT**. This is because X-ray protection curtains made of **optibelt ELASTOMIT-R FDA 115A** are used in quality control in the production lines of renowned food manufacturers (e.g. for protection against fragments of glass or bone) so that you can enjoy your food with peace of mind.



NO COMPROMISE

Speedy, accurate and reliable transport




1. INSPECTION SYSTEMS

Bottles are checked for cleanliness, fractures etc.



3. BEVERAGE FILLING MACHINES

Flawless performance and hygiene are key.



2. BOTTLE SORTING

The right packaging and the product are brought together.



4. CAPPING MACHINE

Precision piecework at high rotational speeds



5. BEVERAGE VENDING

Sophisticated technology for precision tasks.



ISE

The mechanical handling of foodstuffs not only makes high demands with respect to automation technology, but also has to meet stringent hygiene standards. Optibelt offers a special range of timing belts and round belts for this highly sensitive sector. These belts meet the legal requirements and recommendations and are suitable for use in direct contact with food. Further outstanding features of Optibelt's drive solutions include excellent durability and reliability.






6. CUTTING AND PACKAGING MACHINES

High quality standards with regard to cleanliness and efficiency



8. TUBULAR BAGS

The process necessitates speed and precision.



7. TRANSPORT OF FOODSTUFFS (WITH ROUND BELTS)

Everything must work reliably, without stoppages and with perfect timing.




9. FOOD SCANNER

Indispensable for recognising impurities and foreign objects




optibelt ALPHA V

TIMING BELTS



TIMING BELT PULLEYS

all standard pulleys,
special pulleys on request



DIMENSIONS

Available in profiles XL; L; H; XH; T5;
T10; T20; AT5; AT10; AT20; 5M; 8M;
14M; T5K6; T10K6; T10K13; AT5K6;
AT10K6; AT10K13; F2; F2.5; F3; FL3

Minimum lengths of 400 to 1200 mm are
available, depending on width and pitch.

ADVANTAGES AND CHARACTERISTICS

- Lengths can be manufactured according to gradations in pitch
- Can be supplied cost-effectively and at short notice
- Ideal for conveyor drives
- PU also available with FDA approval for food contact
- Direct welding on of cams and cleats possible


optibelt ALPHA V SPECIAL

TIMING BELTS WITH COATINGS



TIMING BELT PULLEYS

all standard pulleys,
special pulleys on request



DIMENSIONS

All belt profiles in the
optibelt ALPHA V product group are
also available as
optibelt ALPHA V SPECIAL profiles.

Minimum lengths of 400 to 1200 mm are
available, depending on width and pitch.

ADVANTAGES AND CHARACTERISTICS

- With coatings
- With mechanical processing
- With cleats


optibelt ALPHA TORQUE

TIMING BELTS AND SPECIAL BELTS



TIMING BELT PULLEYS

all standard pulleys,
special pulleys on request



DIMENSIONS

T2.5; T5; T10/AT5; AT10/DT5;
DT10 120–2250 mm
MXL; XL; L 2.4–67 inches

Special belts on request

ADVANTAGES AND CHARACTERISTICS

- Endless casting
- Extremely resistant to oil and abrasion
- Tension cords made of steel, highly flexible steel, stainless steel, aramid or polyester are available

optibelt RR/RR Plus/HRR

PLASTIC ROUND BELTS



PULLEYS: SEE BROCHURE
optibelt RR/RR Plus/HRR

DIMENSIONS

Optibelt round belts are available with
various degrees of hardness and different
surface structures and can be manufactured
with diameters ranging from 2 to 20 mm.

Minimum lengths, welded:
200 to 400 mm,
depending on the diameter

ADVANTAGES AND CHARACTERISTICS

- Welding takes place on site. This also applies to the **optibelt RR Plus** version.
- No disassembly of the drive/shafts
- Quick rectification of breakdowns
- Short downtimes
- Immediate availability
- Even faster installation thanks to the **optibelt HRR** connector system


optibelt OMEGA HP

HIGH PERFORMANCE TIMING BELTS



TIMING BELT PULLEYS

optibelt OMEGA
timing belts run on
standard HTD and RPP pulleys



DIMENSIONS

2M HP	74–1224 mm
3M HP	111–1569 mm
5M HP	180–2525 mm
8M HP	288–3600 mm
14M HP	966–4578 mm

More profiles and dimensions
on request

ADVANTAGES AND CHARACTERISTICS

- Suitable for low and high speed drives with high dynamic loading
- Shear-resistant fabric with minimised wear and friction
- Up to twice the power transmission capability of the **optibelt OMEGA** Standard version
- Not suitable for direct contact with or transport of foodstuffs


optibelt ALPHA TORQUE SPECIAL/ZR SPECIAL

COATED AND MECHANICALLY PROCESSED TIMING BELTS



TIMING BELT PULLEYS

all standard pulleys,
special pulleys on request



PRODUCT SPECIFICATIONS

optibelt SPECIAL belts have a coating on the top surface and undergo additional mechanical processing.

The wide range of coatings and finishing options combined with the features of the timing belt allow innovative solutions to be developed for conveyor applications.

optibelt ELASTOMIT-R FDA 115A

X-RAY PROTECTION SHEET



PRODUCT SPECIFICATION

Matrix	Rubber
Colour	Black and blue
Surface finish	Coated
Lead equivalent	From 0.12 mm Pb
Mass per unit area	Min. 2000 g/m ²
Tear resistance	60daN/25 mm
Temperature resistance	-40°C to +70°C

ADVANTAGES AND CHARACTERISTICS

- FDA conformity in accordance with test 21 CFR 177.2600 (e) and 177.26000 (f)
- Good temperature resistance
- High flexibility
- High wear resistance thanks to extremely smooth surface
- Coated on both sides
- With reinforcing fabric inlay


optibelt OPTIMAT PKR

OPEN ENDED V-BELTS



V-GROOVED PULLEYS

all standard pulleys,
special pulleys on request



VERSIONS

Z/10; A/13; B/17; C/22; 25*; D/32*

*Special versions are available only in fabrication lengths of 50 m ±10%.

For profiles 25 and D/32, only a top surface height of 5 mm is possible.

ADVANTAGES AND CHARACTERISTICS

- Quick and easy installation
- Manufactured to any length
- Stock of spare parts is reduced
- Classic V-groove power transmission
- Can be used with DIN/ISO V-belt pulleys
- Not suitable for direct contact with or transport of foodstuffs

COMPREHENSIVE SERVICE WITH THE OPTIBELT TEAM



CLEAT SELECTOR

Optibelt provides quick and clearly structured access to its comprehensive range of cleats via the cleat selector on the company's website. This tool can be used to search for or adapt the right transport solution according to the type of application, with a standard range of more than 300 different cleat models to choose from. The search results show all of the available cleat versions with detailed illustrations and the relevant technical data. Each match can then be downloaded with all of the associated information in the form of PDF or CAD files.



DATA SHEET SELECTOR

The data sheet selector provides a detailed overview of the Optibelt range of PU timing belts for "POWER TRANSMISSION" and "MATERIAL HANDLING". This online tool, available on the Optibelt website, can be used to download PDF files giving technical details of the required timing belts. The search can be narrowed down according to product, profile group and profile in order to find the ideal drive solution more directly. The corresponding data sheet provides precise information on dimensions, construction, nominal transmittable power, tensile force and length tolerances.



PRODUCT FINDER

An overview of our products and their combination with tension cords and fabrics. Selectable by dimensions, industry sector and belt section.

Optibelt Material Handling GmbH

Im Emerten 11

31737 Rinteln

GERMANY

T +49 (0) 57 51 -9 67 79-0

F +49 (0) 57 51 -9 67 79-10

E info-omh@optibelt.com

